



### Type VA 210

2-way solenoid valve  
direct actuated, NC  
(normally closed)



**Application**  
Neutral and mildly aggressive  
liquids, gases and vapors



Type/ Order No.	Orifice [mm]	Port size	Pressure range [bar]		kv-value [m³/h]	Weight [kg]
			AC	DC		
VA 210-001	0,8	M 5	-	0 - 8	0,02	0,050
VA 210-002	1,0	M 5	-	0 - 6	0,03	0,050
VA 210-003	1,2	M 5	-	0 - 5	0,04	0,050
VA 210-004	1,6	M 5	-	0 - 2	0,06	0,050
VA 210-005	2,0	M 5	-	0 - 1	0,08	0,050

Sealing material: **E** (EPDM) **V** (FPM) **Z** (FFPM)

Body material: Stainless steel (1.4305)  
 Inner parts: Stainless steel (1.4105)  
 Mounting direction: Free, preferred upwards  
 Max. ambient temp.: 50 °C  
 Viscosity of the medium: max. 21 mm²/s (3 °E)  
 Static pressure: max. 30 bar  
 Standard voltage: DC: 24, 12 V

Power consumption: 1 W  
 Voltage tolerance: -15%... +10%  
 Duty cycle: 100%  
 Operating frequency: max. 1800/min  
 Degree of Protection: IP 54 (EN 60529)

The right to modification is reserved

