


Type ZV

Switch-on delay



Application
Solenoid valves with pin connectors standard to DIN 43650



Time range t_{off}

| | | | |
|-------|-------------|--------|--------------------|
| 1 S | 0,1 s... | 1 s | (Step size 10 ms) |
| 5 S | 0,1 s... | 5 s | (Step size 50 ms) |
| 10 S | 0,1 s... | 10 s | (Step size 100 ms) |
| 30 S | 0,3 s... | 30 s | (Step size 300 ms) |
| 100 S | 1,0 s... | 100 s | (Step size 1 s) |
| 5 M | 3,0 s... | 5 min | (Step size 3 s) |
| 10 M | 6,0 s... | 10 min | (Step size 6 s) |
| 30 M | 18,0 s... | 30 min | (Step size 18 s) |
| 1 H | 36,0 s... | 1 h | (Step size 36 s) |
| 24 H | 15,0 min... | 24 h | (Step size 15 min) |

Connector

SAW DIN 43650 - A
SAD DIN 43650 - B
SAH DIN 43650 - BI

Time adjustment t_{off}

F Fixed
V Adjustable with potentiometer

Voltage range

DC 12–30 VDC
AC 115–230 VAC/50–60 Hz

Housing material: Polyamid black
Ambient temp. range: 0... +60 °C
Display: LED switch on / off
Degree of protection (EN 60529): IP 65 (installed)

Power consumption: 1 W
Max. load current: 0,5 A (AC), 1 A (DC)
Output voltage: min. U_B -2V
Switching time tolerance: ±5% of full scale time range

Order code see page 368

362

Other configurations upon request






Switch-on delay



SAW

SAH

SAD



Dimensions in mm

The right to modification is reserved

363